

FL 190A

Instantly self-levelling



TECHNICAL DATA	FL 190A	FEATURES	SUPPLIED WITH FL 190A (LC 2)
Self-levelling range	± 3°	<ul style="list-style-type: none"> Instant self-levelling Horizontal self-levelling rotating laser; vertical levelling with one footscrew Automatic shut-off and audible alarm when out of self-levelling range Variable rotating speed Permanent 90° beam to zenith Rechargeable NiMH batteries with intelligent charger Integrated floor / wall mount with adjustment screw 	ART.-NO. 292190 <ul style="list-style-type: none"> Receiver FR 45 with clamp for levelling staff NiMH batteries Charger Carrying case
Accuracy	± 1,5 mm / 10 m		
Working range without receiver Ø	30 m*		
Working range with receiver Ø	400 m		
Rotating speed (rpm)	200, 400, 600		
Power supply	NiMH		
Operating time	12 h		
Dust / water protection	IP 54		
Laser diode / class	635 nm / 2		
Temperature range	-10°C to +45°C		
Weight (instrument with battery)	1,5 kg		
	* depending on the room illumination		

SUPPLIED WITH FL 190A (LC 2)
ART.-NO. 292193 <ul style="list-style-type: none"> Receiver FR-DIST 30 with clamp for levelling staff NiMH batteries Charger Carrying case