

S-Digit 60WL + and S-Digit 120WL +



TECHNICAL DATA		S-DIGIT 60WL +	S-DIGIT 120WL +	FEATURES
ART.-NO.		640010	640110	
Working range		4 x 90°	4 x 90°	· Different signal tones when approaching 0° / 90° and continuous tone at 0° / 90° · Inclination direction indication · Zero position re-set at any position · Automatic digit inversion for overhead measurements · 180° rotatable display · HOLD function to freeze measurement · Illuminated display · 1 or 2 recessed hand grips for ergonomic use
Resolution		0,1° / 0,1 %	0,1° / 0,1 %	
Accuracy		0° and 90° = ± 0,1°	0° and 90° = ± 0,1°	
		1° and 89° = ± 0,2°	1° and 89° = ± 0,2°	
Measuring units / display		°, %, mm/m, in/ft	°, %, mm/m, in/ft	
Power supply		3 x AAA Alkaline	3 x AAA Alkaline	
Operating time		60 h	60 h	
Temperature range		-10 °C to +45 °C	-10 °C to +45 °C	
Weight		0,93 kg	1,2 kg	
Dimensions		600 x 60 x 27 mm	120 x 60 x 27 mm	
SUPPLIED WITH				S-DIGIT 60WL + / 120WL +
				· Padded bag · Batteries